



Model No.: F27 4G Wifi Dongle(150Mbps DL / 50Mbps UL)

| | | |
|---------------------|------------------------------------|--|
| Chipset | Qualcomm MSM8916 | |
| Network supported | Default version | 4G FDD LTE B1/B3/B5 WCDMA:B1(2100MHz)/B5(850MHz) |
| | Europe version | 4G FDD LTE B1/B3/(B5)/7/8/20+TDD B38/40/41 WCDMA:B1(2100MHz)/B5(850MHz) |
| | CN version | 4G FDD LTE B1/B3/(B5)/8+TDD B38/39/40/41 WCDMA:B1(2100MHz)/B5(850MHz) |
| Wifi | support 10 users to share the wifi | |
| | 802.11b/g/n, speed upto 150Mbps | |
| | 2412MHz-2472MHz | |
| Speed | FDD LTE | up to 150Mbps DL / up to 50Mbps UL |
| | HSDPA | up to 42.2Mbps DL |
| | HSUPA | up to 11.5Mbps UL |
| 3GPP | FDD LTE | 3GPP R9 Cat.4 |
| | TDD LTE | 3GPP R9 Cat.4 |
| | HSDPA | 3GPP R7&R8 Cat.24(64QAM) |
| | HSUPA | 3GPP R7&R8 Cat.7(16QAM) |
| Port | USB | 1 |
| | USIM/SIM | 1 |
| Others | Hardware interface | USB interface |
| | Sensitivity | <-105dBm (FER≤0.5%) |
| | Working voltage | 5V DC |
| | Working current | 280~1000mA |
| | Sleep Current | <50mA |
| | Language | English |
| | dimension | 96*35*13mm |
| | weight | 29g |
| working temperature | -10 to +55℃ | |

| | |
|---------------------|--------------|
| working humidity | 10% to 80% |
| storage temperature | -20 to +60°C |
| storage humidity | 5% to 90% |