



Model No.: V16S 4G Wifi Dongle(150Mbps DL / 50Mbps UL)

Chipset	ASR1803S	
Network supported	CN version	LTE-FDD B1/B3/B5/B8+TDD B34/B38/B39/B40/B41 WCDMA:B1/B5/B8
	AU version	LTE-FDD B1/B3/B5/B7/B8/B20/B28+TDD B38/B40/B41 WCDMA:B1/B5/B8
	AM version	LTE-FDD B1/B2/B3/B4/B5/B7/B8/B20/B26/B28/B66+TDD B38/B40/B41 WCDMA:B1/B2/B4/B5/B8
Antenna	4G main antenna	1
	4G diversity antenna	1
	WiFi antenna	1
WiFi	support 10 users to share the wifi	
	802.11b/g/n, speed upto 150Mbps	
	2412MHz-2472MHz	
Speed	FDD LTE	up to 150Mbps DL / up to 50Mbps UL TDD can be added
	HSDPA	up to 42.2Mbps DL
	HSUPA	up to 11.5Mbps UL
3GPP	FDD LTE	3GPP R9 Cat.4(TDD LTE can be added)
	HSDPA	3GPP R7&R8 Cat.24(64QAM)
	HSUPA	3GPP R7&R8 Cat.7(16QAM)
Port	USB	1
	USIM/SIM	1
Others	Hardware interface	USB interface
	Sensitivity	<-105dBm (FER≤0.5%)
	Working voltage	5V DC
	Working current	280~1000mA
	Sleep Current	<50mA
	Language	English
	dimension	89x29x10mm
	weight	25g
working temperature	-10 to +55°C	

working humidity	10% to 80%
storage temperature	-20 to +70°C
storage humidity	5% to 90%