



<b>Model No.:P28</b>	<b>4G CPE speed up to 150Mbps</b>
CPU	•CPU: ZT7520V3E/T/Qualcomm9x07 or ASR1803S
Network	<ul style="list-style-type: none"> <li>•4G LET 3GPP R9 CAT.4 •Transfer rate up to 150Mbps</li> <li>•4G FDD B1,B3,B5,B8(can add more frequency such as B5,B7,B8,B20,etc.)</li> <li>•4G TDD B38,B39,B40,B41</li> <li>•WCDMA:B1,B5,B8</li> <li>• TD-SCDMA:B34,B39</li> </ul>
Wi-Fi	<ul style="list-style-type: none"> <li>•IEEE 802.11b/g/n/ac support 2.4G</li> <li>•Wi-Fi Protected Access™ (WPA/WPA2)2</li> </ul>
Ports	<ul style="list-style-type: none"> <li>•1* USB Type C</li> <li>•1* 2FF SIM+ 1 esim</li> <li>•1* LAN or 1WAN+2LAN for option</li> <li>•1* Reset</li> <li>•2*4G antenna, 1 WIFI antenna</li> </ul>
Environment	<ul style="list-style-type: none"> <li>•working: -20° to 50°C (-4° to 122°F)</li> <li>•storage: -40° to 85°C (-40° to 185°F)</li> </ul>
Dimension	•166.0*120.2*40.2mm
Weight	•300g(including antenna)



型号:P28

CPU

网络制式

Wi-Fi

接口

环境

尺寸

重量



### 4G CPE路由器 150Mbps

- CPU: ZT7520V3E/T/Qualcomm9x07 or ASR1803S
- 4G LET 3GPP R9 CAT.4 •Transfer rate up to 150Mbps
- 4G FDD B1,B3,B5,B8(can add more frequency such as B5,B7,B8,B20,etc.)
- 4G TDD B38,B39,B40,B41
- WCDMA:B1,B5,B8
- TD-SCDMA:B34,B39
- IEEE 802.11b/g/n/ac support 2.4G
- Wi-Fi Protected Access™ (WPA/WPA2)2
- 1\* USB Type C
- 1\* 2FF SIM+ 1 esim
- 1\* LAN or 1WAN+2LAN for option
- 1\* Reset
- 2\*4G antenna, 1 WIFI antenna
- working: -20° to 50°C (-4° to 122°F)
- storage: -40° to 85°C (-40° to 185°F)
- 166.0\*120.2\*40.2mm
- 300g